

Patents

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

TAE JIN EOM ET AL.

Serial No.: 08/239,313

Filed: May 6, 1994

For: **BIOLOGICAL DE-INKING METHOD)**

Art Unit: 1303

Examiner: K. Hastings

DECLARATION OF KARL-ERIK L. ERIKSSON, PH.D.

UNDER 37 CFR § 1.132

KARL-ERIK L. ERIKSSON, PH.D., declares as follows:

1. I earned a Dr. Sci. in biochemistry in 1967. Subsequently, I have conducted extensive research in the fields of enzymology, microbiology and biochemistry. I am currently a Professor of Biochemistry and Eminent Scholar at the University of Georgia, Athens, Georgia. Attached is a copy of my Curriculum Vitae.

2. My declaration is based on my scientific experience and understanding of the subject matter as an expert in the art. I am familiar with the invention described in the above-identified patent application regarding the novel use of deinking enzymes under non-alkali conditions. For the record, I have a very small economic interest in the business concern that has licensed the subject invention .

3. I have read the English translation of Japanese Patent 59-9299 ('299 patent). In my expert opinion, the '299 patent, read in its entirety, teaches one of ordinary skill in the art only the successful use of deinking enzymes with alkaline deinking chemicals. It is my opinion that the data provided in the '299 patent, taken together with the knowledge of one skilled in the art prior to the priority date of the present application of May 16, 1989, does not provide an expectation for the

DECLARATION OF KARL-ERIK L. ERIKSSON, PH.D.

successful use of enzymes for removing ink from pulp in a non-alkali environment, in particular at a pH of between about 3 to about 8.

4. This is true because the overall thrust of the '299 patent specification, and the evidence provided in all preferred embodiments and in all the Examples, refer to only alkali deinking conditions. The statement on page 3, lines 1-5, that "Such enzyme retains its activity in the alkaline range as well as the acid or neutral range, e.g. a product purified and fractionated from cellulase culture liquid of various origins by salting out, precipitation, dialysis and gel fractionation..." refers to the conditions under which the enzyme may be purified, and does not suggest the use of the enzyme for deinking under non-alkaline conditions. Even if one were to interpret the statement to indicate the use of the enzyme under non-alkaline conditions, one skilled in the art would not have expected a successful result deinking under non-alkaline conditions, for the reasons described below. The only scientifically supported statements in the '299 patent are directed to the use of deinking enzymes in alkali conditions.

5. Before the description in the above-identified patent application, it was believed that alkaline conditions were necessary for deinking enzymes to cause ink containing paper fibers to swell to effect defiberization and deinking. Absent alkaline conditions, one would not have expected swelling, and therefore deinking, to occur as a result of the addition of deinking enzymes alone in the pulping process. In the deinking art there is over twenty years of published detailed studies from commercial, academic and government laboratories that emphasize that chemical modification and treatment by alkali exposure is essential and necessary for deinking. As a recent example, enclosed is a copy of the Paper and Pulp International (PPI) publication entitled "Neutral Deinking Makes Its Debut," describing the breakthrough in October 1993 of deinking in neutral conditions, without the addition of alkalis such as sodium hydroxide to the pulp prior to or during deinking.

DECLARATION OF KARL-ERIK L. ERIKSSON, PH.D.

6. Therefore, to one skilled in the deinking art at the time the above-identified application was originally filed, the deinking action of enzymes in a non-alkaline medium would have been extremely novel and surprising. An expectation of the successful use of deinking enzymes in an aqueous medium having a pH of between about 3 to about 8 is not found in the '299 patent. It is my opinion that prior to the invention described in the above-identified patent application, no one skilled in the art would waste time, money or effort in evaluating deinking enzymes alone without the addition of alkalis.

7. In summary, it is my expert opinion that the disclosure of the '299 patent supports only the deinking of waste papers by the use of chemical alkaline deinking agents and cellulase, and does not provide a basis for the successful use of cellulase deinking enzyme in an aqueous medium having a pH of less between about 3 to about 8 with an expectation of successful deinking of waste paper.

6. The undersigned declares that all statements made herein of his own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements are made with the knowledge that willful false statements and the like are punishable by fine or imprisonment or both under 18 U.S.C. § 1001, and that such willful false statements may jeopardize the validity of the above-referenced application or any patent issuing thereon.

Febr. 16, 1998
DATE

Karl-Erik Eriksson
KARL-ERIK L. ERIKSSON, PH.D.

Patents

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
)
TAE JIN EOM ET AL.)
)
Serial No.: 08/239,313) Art Unit: 1303
)
Filed: May 6, 1994) Examiner: K. Hastings
)
For: BIOLOGICAL DE-INKING METHOD)	

DECLARATION OF DOUGLAS E. EVELEIGH, PH.D.

UNDER 37 CFR § 1.132

DOUGLAS E. EVELEIGH, PH.D., declares as follows:

1. I am an expert in the areas of enzymology and biochemistry. I am currently a Professor in the Department of Microbiology at Rutgers, the State University, New Brunswick, New Jersey. Attached is a copy of my Curriculum Vitae.
2. My declaration is based on my scientific experience and understanding of the subject matter as an expert in the art. I am familiar with the invention described in the above-identified patent application regarding the novel use of deinking enzymes under non-alkali conditions.
3. I have read the English translation of Japanese Patent 59-9299 ('299 patent). In my expert opinion, the '299 patent, read in its entirety, teaches one of ordinary skill in the art only the successful use of deinking enzymes, either concurrently or sequentially, with alkaline deinking chemicals. It is my opinion that the '299 patent does not provide to those skilled in the art an

DECLARATION OF DOUGLAS E. EVELEIGH, PH.D. UNDER 37 CFR § 1.132

expectation for the successful use of enzymes for removing ink from pulp in a non-alkali environment, in particular at a pH between about 3 to about 8.

4. This is true because the '299 patent only provides actual data for embodiments of deinking newspapers in alkali conditions in Examples 1-3 on pages 4-10. The emphasis and all preferred embodiments refer to alkali deinking. "Such enzyme retains its activity in the alkaline range as well as the acid or neutral range, e.g. a product purified and fractionated from cellulase culture liquid of various origins by salting out, precipitation, dialysis and gel fractionation..." refers to the conditions under which the enzyme may be purified, and does not suggest the use of the enzyme for deinking under non-alkaline conditions. Even if one were to interpret the statement to indicate the use of the enzyme under non-alkaline conditions, one skilled in the art would not have expected a successful deinking result under non-alkaline conditions, for the reasons described below. The only scientifically supported statements in the '299 patent are directed to the use of deinking enzymes in alkali conditions.

5. One skilled in the art would not expect deinking enzymes to work in non-alkali conditions, i.e. at a pH between about 3 to about 8, because in the deinking art there is over twenty years of published detailed studies from commercial, academic and government laboratories that emphasize that chemical modification and treatment by alkali exposure is essential and necessary for deinking. Prior to the description in the above-identified patent application, it was believed that alkaline conditions were necessary for deinking enzymes to cause ink-containing paper fibers to swell to effect defiberization and deinking. Absent alkaline conditions, one would not have expected swelling, and therefore adequate ink detachment and removal, to occur as a result of the addition of deinking enzymes alone in the pulping process.

DECLARATION OF DOUGLAS E. EVELEIGH, PH.D. UNDER 37 CFR § 1.132

6. Therefore, to one skilled in the deinking art at the time the above-identified application was originally filed on May 16, 1989, the deinking action of enzymes in a non-alkaline medium would have been extremely novel and surprising. In my opinion, an expectation of the successful use of deinking enzymes in an aqueous medium having a pH between about 3 to about 8 is not found in the '299 patent.

7. In summary, it is my expert opinion that the disclosure of the '299 patent supports only the deinking of waste papers by the use of chemical alkaline deinking agents and cellulase, and does not provide a basis for the successful use of cellulase deinking enzyme in non-alkaline conditions to deink waste papers. It is clear to me that prior to the disclosure of the above-identified application, any person skilled in the use of deinking enzymes would not use deinking enzymes to pulp waste paper in an aqueous medium having a pH of between about 3 to about 8 with an expectation of successful deinking of waste paper.

8. The undersigned declares that all statements made herein of his own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements are made with the knowledge that willful false statements and the like are punishable by fine or imprisonment or both under 18 U.S.C. § 1001, and that such willful false statements may jeopardize the validity of the above-referenced application or any patent issuing thereon.

16 Feb 1998
DATE

Douglas E. Eveleigh
DOUGLAS E. EVELEIGH, PH.D.

Suppliers of deinking systems are working to meet the demand for high-quality paper made from low-quality waste. Amanda Marcus rounds up the latest developments and lists new orders worldwide.

ATTACHMENT 1

Neutral deinking makes its debut

SOME RECENT AND PLANNED DEINKING INSTALLATIONS¹

Country	Company	Mill location	Startup date	Capacity (1,000 tons/yr)	Wastepaper	Grade	End-use Supplier
Australia	Australian Newsprint Mills	Lavington, NSW	1993	122.5*	News/magazines	Newsprint	Voith
Austria	Leykam-Mühlbacher	Graz	1993	40*	News/magazines	Newsprint	Voith ²
Argentina	Celulosa Campana	Zarate	1994	45.5	Mixed waste	Tissue	Sulzer Papertec
Argentina	Papel Prensa	Buenos Aires	1993	21	Waste	Newsprint	Lamort
Canada	Alberta Newsprint	Whitecourt	1993	21*	News/magazines	Newsprint	Voith ³
Canada	QUNO (Quebec & Ontario Pap)	Thorold	1993	70*	News/magazines	Newsprint	Voith ³
Canada	Spruce Falls Power & Paper	Kapuskasing	1993	87.5*	Old news/pamphlets	Newsprint	Voith ³
China	Guangzhou Paper	Guangzhou	1993	32	Ledgers	Fine paper	Black Clawson
China	Harzhong Pulp & Paper	-	1994	9	Waste	Whiteboard base	Lamort/Aikawa
China	Xuecheng Huazhong Paper	-	1993	9	Waste	Whiteboard base	Lamort/Aikawa
China	Yanjin Paper	Nanjing	1994	35*	News/magazines	Newsprint	Sulzer
France	Chapelle Darblay	Port Audemer	1993	6	Ledgers	Fine paper	Black Clawson
Germany	Dresden Papier	Freital	1994	42	News/magazines	Graphic papers	Sulzer Papertec
Germany	Palm	Eitmann	1994	168	News/magazines	Newsprint	Sulzer Papertec
Germany	Sachsen Papier	Eilenburg	1994	350	News/magazines	Newsprint	Sulzer Papertec
Germany	Schweidt Pap. und Karton	Schweidt	1994	143.5	News/magazines	Graphic papers	Sulzer Papertec

1: This list is not intended to be comprehensive. Orders since the last PPI Deinking Survey in October 1992. 2: Built by Voith St. Pölten, Austria, a Voith licensee. 3: Built by Voith Appleton, USA, a Voith licensee. 4: Andritz was acting as a licensee of Sulzer Papertec, Germany. * = Calculated from daily capacity, on the basis of 350 production days/yr.

Continued on page 24

WASTE IS NO LONGER a dirty word. On the contrary, an increasing number of consumers, and hence paper-makers, can't seem to get enough of it. According to PPI statistics (see table), the world recovered almost 92 million tons of wastepaper in 1992, up from 87 million tons in 1991, and consumed 95.5 million tons, four million tons more than the previous year. The world's average utilization rate has risen by two points to 39%.

From Argentina to Austria, and Mexico to Morocco, the latest reference lists from suppliers (see above) show that mills are still spending money on waste treatment systems, even during a time of severe cutbacks in capital investment in the industry. Increasing environmental legislation and stringent quality requirements are demanding rapid developments from manufacturers of deinking equipment. This article rounds up the latest news from some of the sector's major suppliers.

All agree that differences in customer demands in Europe and North America are narrowing. Black Clawson, USA, reports

that US customers are beginning to look at the European approach to projects, looking for more liability from the supplier to make the system perform. "As more of these projects come under study, it is becoming apparent that the vendor's ability to provide special financing or equity participation is becoming as important as the technological issues that have always faced us," comments Black Clawson.

The parameters of evaluation from the customers' viewpoint are basically the same: All mills are seeking price performance, higher brightness, dirt reduction, ash control and higher yields from their systems: no mean task for suppliers.

Customers want more for less

One of the major challenges facing suppliers of wastepaper treatment systems is that mills are using lower-quality and hard-to-deink waste while requiring ever-higher quality. As a result, according to Black Clawson, research in the USA is focusing largely on the removal of difficult-to-handle debris that is typically

grade office papers: unbleached fibers, laser-printing inks, UV coatings and some dyed papers. The supplier adds that it is only a matter of time before the same concerns are transferred to system designers in the European and Asian markets.

Mills get into neutral gear

Neutral deinking is being hailed as the latest breakthrough in waste treatment technology by Lamort of France. It says that the benefits of deinking in neutral media are proving to be far beyond initial expectations. Such a solution is attractive because it requires less chemicals, so chemical oxygen demand is reduced and companies save on chemical costs. Suppliers to the industry say that controllability, drainage, pulp strength, bleachability and screening efficiency are all better than with conventional deinking techniques.

The Stephenson Group, UK, which supplies deinking chemicals, agrees that demand for neutral deinking solutions and closed-water circuits is growing. Customers want to use lower and lower grades of

PPI October 1993

DEINKING SURVEY/WP TRADE

wastepaper for deinking, comments the company, and this is leading to problems with product quality (both brightness and stickies), which the customer expects the supplier to solve.

In response, a considerable amount of resources is being invested in upgrading washing systems as part of a "complete ink removal" solution provided by a combined wash/flotation system. Cost is the limiting factor, explains Stephenson, but work on the concept is continuing.

The first neutral deinking system using household waste to make graphic papers is already in operation at Zwingen in Switzerland. The line started up last July and is the result of a joint project between the mill, French supplier Lamort, and Dr. W. Kolb. Lamort explains that since the process does not use sodium hydroxide, an efficient fiber-to-fiber friction is imperative if good ink removal is to be achieved at the pulping stage, although post-flotation is still available. Lamort recommends its Helico pulper for such applications.

Waste is floating on air

Neutral flotation is quite different to

conventional deinking in that the ink particles adhere directly to the air bubbles, Lamort explains. The foam structure of the cell is also completely different. Consequently, demand is growing for a flotation cell which can handle an increased number of smaller bubbles and separate foam from fiber. Lamort's response is the Verticel which works on the concept of injection and has a controlled flow pattern.

Lamort says that Verticel has a foam-removal system which is particularly suited to neutral deinking.

Voith, Germany, is also continuing work on flotation and has recently launched its new laboratory flotation cell type E, a reduced version of the industrial unit. Five have already been sold.

Voith's flotation machine consists of a mixing tank followed by primary and secondary stages with the secondary stage being used to recover useful fibers from the overflow of the primary stage. Each stage is composed of tubular cells arranged in series, the number and size of which depend on the flotation behavior of the printing inks and on the throughput.


According to the supplier, the unit's

main advantages lie in maximum brightness with low energy consumption and an above-average purity of deinked stock, due to multiple, consistent, forced ventilation of each cell. Flotation is accelerated because air supply is increased, requiring fewer cells, explains the supplier.

Black Clawson is working with its licensee in Japan, IIM, on the new IIM-BC Flotator flotation cell. According to the supplier, the key to the unit's performance is its ability to mix uniformly high volumes of air into the stock slurry so that maximum brightness and dirt speck removal can be achieved. The air bubbles that are generated by the twin turbines in each cell are evenly distributed across the spectrum of sizes needed to optimize particle-removal efficiency, from 5-500 microns.

Black Clawson claims that the Flotator can improve brightness by 14 points in a single pass, and that it has shown improved speck removal efficiency, even with hard-to-deink grades such as laser-printed office papers or UV-coated grades. The supplier intends to market the Flotator unit on both sides of the Atlantic.


WHEN IT COMES TO B WE'RE AS VERSATILE AS



If you're after a complete paper mill, mill refurbishment, paper machine or process system

rebuild, talk to Simon-Holder.

The strong technology base within Simon-Holder enables us to meet your market needs, using the key technologies of de-



ARE you still well, while y little exercise those scenery identifies. It most importa. JAMMUM GAY. NUMBER 1001

World-wide, we

are leaders in th design and build of paper mills and specialise

in the extension and refurbishment of existing facilities. We custom engineer quality and production improvements associated with machine rebuilds to ensure the most cost effective solutions.

We offer a full project

